


Midget – Locking

		15 AMPERE	
		RECEPTACLE	PLUG
<b>2 Pole, 2 Wire Non-Grounding</b>			
125V	ML1		
<b>2 Pole, 3 Wire Grounding</b>			
125V	ML2		
<b>3 Pole, 3 Wire Non-Grounding</b>			
125/250V	ML3		

Labels & Their Meaning

X, Y, Z	Hot Lead
W	Neutral Lead
G	Grounding Lead

Open Slots  
Indicate receptacle configurations (female).



Closed Slots  
Indicate plug blade configurations (male).



Locking Plugs & Receptacles

		15 AMPERE		20 AMPERE		30 AMPERE	
		RECEPTACLE	PLUG	RECEPTACLE	PLUG	RECEPTACLE	PLUG
<b>2 Pole, 2 Wire Non-Grounding</b>							
125V	L1						
250V	L2						
<b>2 Pole, 3 Wire Grounding</b>							
125V	L5						
250V	L6						
277VAC	L7						
347VAC	L24						
480VAC	L8						
600VAC	L9						
<b>3 Pole, 3 Wire Non-Grounding</b>							
125/250V	L10						
3ø250V	L11						
3ø480V	L12						
3ø600V	L13						
<b>3 Pole, 4 Wire Grounding</b>							
125/250V	L14						
3ø250V	L15						
3ø480V	L16						
3ø600V	L17						
<b>4 Pole, 4 Wire Non-Grounding</b>							
3øY 120/208V	L18						
3øY 277/480V	L19						
3øY 347/600V	L20						
<b>4 Pole, 5 Wire Grounding</b>							
3øY 120/208V	L21						
3øY 277/480V	L22						
3øY 347/600V	L23						